

## **Safety Data Sheet**

# 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name	Beryllium(II)sulfate tetrahydrate 1.0% pet
Article Number	B-044
Applications	Diagnosis of contact allergy.
Manufacturer	Chemotechnique MB Diagnostics AB Modemgatan 9 SE-235 39 Vellinge lab@chemotechnique.se
Telephone Fax	+46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1) +46 (0) 40 466 700

#### 2. HAZARD IDENTIFICATION

#### Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

#### Signs and symptom of exposure

Dermal irritation.

Medical conditions aggravated by exposure Dermatitis.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]				
Component	CAS-No.	Content	Classification	
Petrolatum	8009-03-8	99.0%	-	
Beryllium(II)sulfate	7787-56-6	1.0%	Acute tox. Oral 3, Acute tox. Inhal. 2,	
tetrahydrate			Skin irrit. 2, Eye irrit. 2, Skin sensit. 1,	
			Carc. Inhal. 1B, Spec. targ. org. tox	
			single exp. 3, Spec. targ. org. tox. –	
			rep. exp. 1, Chron. aq. tox. 1; H301,	
			H315, H317, H319, H330, H335,	
			H350i, H372, H411	

Classification according to EU Directive 67/548/EEC and 1999/45/EC Component CAS-No. Content Classification

Petrolatum	8009-03-8	99.0%	-
Beryllium(II)sulfate	7787-56-6	1.0%	T+, T, Xi, N; R49, R26, R25, R48/23,
tetrahydrate			R36/37/38, R43, R51/53

#### 4. FIRST AID MEASURES

**Emergency and first aid procedures** Obtain medical attention.

#### 5. FIRE-FIGHTING MEASURES\*

#### Suitable extinguish media

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents Water with full jet.

**Special protective equipment for fire-fighters** Wear self-contained respiratory protective device. Wear fully protective suit.

\*Data is shown for petrolatum only

#### 6. ACCIDENTAL RELEASES MEASURES

Steps to be taken if material is released or spilled Contain and place in a closed container.

#### 7. HANDLING AND STORAGE

**Precautions to be taken in handling and storage** Store dark at 5-8°C. Avoid extended exposure to light. FOR EXTERNAL USE ONLY.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Respiratory protection** Not required.

#### Ventilation Local exhaust.

### Protective gloves

Disposal gloves.

#### Eye protection

Not required with normal use.

#### Work/Hygienic practices

Wash hands after each use.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Page 2/4

Appearance	Ivory White Semi Solid
Odour	Odourless
Melting point* Boiling point* Flash point* Self ignition* Danger of explosion* Density* Solubility in/Miscibility with Water*	50-55° C No data available >100°C Product does not self ignite. Product does not present an explosion hazard. No data available. Insoluble

\*Data is shown for petrolatum only

#### **10. STABILITY AND REACTIVITY**

#### Incompability

May react with strong oxidizing agents.

Stability

Stable at recommended storage conditions.

#### Hazardous byproducts

Combustion may generate CO, CO2 and other oxides.

Hazardous polymerization

Will not occur.

#### 11. TOXICOLOGICAL INFORMATION

No data available.

#### 12. ECOLOGICAL INFORMATION

No data available.

#### 13. DISPOSAL CONSIDERATIONS

Waste disposal method Comply with federal, state/provincial and local regulation.

#### 14. TRANSPORT INFORMATION

Not dangerous goods.

#### 15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

#### 16. OTHER INFORMATION

#### Text of H-statements and R-phrases mentioned in Section 3

Acute tox. Oral 3 Acute tox. Inhal. 2 Skin irrit. 2 Eye irrit. 2	Acute toxicity, Oral (Category 3) Acute toxicity, Inhalation (Category 2) Skin irritation (Category 2) Eye irritation (Category 2)
Skin sensit. 1	Skin sensitization (Category 1)
Carc. Inhal. 1B	Carcinogenicity, Inhalation (Category 1B)
Spec. targ. org. tox single exp. 3	. Specific target organ toxicity - single exposure (Category 3)
Spec. targ. org. tox. – rep	Specific target organ toxicity - repeated exposure (Category
exp. 1	1)
Chron. aq. tox. 1	Chronic aquatic toxicity (Category 1)
H301	Toxic if swallowed.
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H330	Fatal if inhaled.
H335	May cause respiratory irritation
H350i	May cause cancer by inhalation.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
T+	Very Toxic
Т	Toxic
Xi	Irritant
Ν	Dangerous for the environment.
R49	May cause cancer by inhalation
R26	Very toxic by inhalation
R25	Toxic if swallowed
R48/23	Toxic: danger of serious damage to health by prolonged
	exposure through inhalation
R36/37/38	Irritating to eyes, respiratory system and skin
R43	May cause sensitisation by skin contact
R51/53	Toxic to aquatic organisms, may cause long-term adverse
	effects in the aquatic environment

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.