



Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name	Basic Red 46 1.0% pet
Article Number	B-026
Applications	Diagnosis of contact allergy.
Manufacturer	Chemotechnique MB Diagnostics AB Modemgatan 9 SE-235 39 Vellinge lab@chemotechnique.se
Telephone	+46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1)
Fax	+46 (0) 40 466 700

2. HAZARD IDENTIFICATION

Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

Signs and symptom of exposure

Dermal irritation.

Medical conditions aggravated by exposure

Dermatitis.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]

Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8	99.0%	-
Basic Red 46		1.0%	Acute tox. Oral 4, Serious eye dam.1, Chron. aq. tox. 1; H302, H318,H411

Classification according to EU Directive 67/548/EEC and 1999/45/EC

Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8	99.0%	-
Basic Red 46		1.0%	Xn, N; R22, R41, R51/53

4. FIRST AID MEASURES

Emergency and first aid procedures

Obtain medical attention.

5. FIRE-FIGHTING MEASURES*

Suitable extinguish media

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents

Water with full jet.

Special protective equipment for fire-fighters

Wear self-contained respiratory protective device. Wear fully protective suit.

*Data is shown for petrolatum only

6. ACCIDENTAL RELEASES MEASURES

Steps to be taken if material is released or spilled

Contain and place in a closed container.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage

Store dark at 5-8 C. Avoid extended exposure to light. FOR EXTERNAL USE ONLY.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

Not required.

Ventilation

Local exhaust.

Protective gloves

Disposal gloves.

Eye protection

Not required with normal use.

Work/Hygienic practices

Wash hands after each use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Dark Red Semi-solid

Odour Odourless

Melting point* 50-55° C

Boiling point* No data available

Flash point* >100°C

Self ignition*	Product does not self ignite.
Danger of explosion*	Product does not present an explosion hazard.
Density*	No data available.
Solubility in/Miscibility with Water*	Insoluble

*Data is shown for petrolatum only

10. STABILITY AND REACTIVITY

Incompability

May react with strong oxidizing agents.

Stability

Stable at recommended storage conditions.

Hazardous byproducts

Combustion may generate CO, CO₂ and other oxides.

Hazardous polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Waste disposal method

Comply with federal, state/provincial and local regulation.

14. TRANSPORT INFORMATION

Not dangerous goods.

15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

16. OTHER INFORMATION

Text of H-statements and R-phrases mentioned in Section 3

Acute tox. Oral 4	Acute toxicity, Oral (Category 4)
Serious eye dam. 1	Serious eye damage (Category 1)
Chron. aq. tox. 1	Chronic aquatic toxicity (Category 1)
H302	Harmful if swallowed

H318	Causes serious eye damage
H411	Toxic to aquatic life with long lasting effects
Xn	Harmful
R22	Harmful if swallowed
R41	Risk of serious damage to eyes
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.